

# Evolution 05 Mini

## 360° Night Camera


The next step in 360° total situational awareness

### 5 MP sensor and no moving parts

- Constant 360° surveillance with no blind spots
- No moving parts, no maintenance and silent operation
- Up to 30 fps video stream at 1 MP and ¼ MP
- 0.2 lux minimum illumination and electronic WDR
- PoE powered
- 5-year warranty

### IR optical filter

- Visible light + near infrared pass-band at 850 NM



### Advanced features

- microSD card slot for local event recording
- Configurable privacy regions
- Polygonal Video Motion Detection regions

### Multiple interior mount options

- Quick and easy installation
- Clean and simple design
- Convenient surface-mounting enclosure
- Range of accessories provide multiple mounting possibilities including ceiling, wall and pendant
- Enclosure available in White



EVO-05-LIN - White

### Extensive VMS/NVR platform integration with Oncam SDK

- Market leading Oncam Grandeye 3D dewarping software
- Full live and retrospective dewarping available
- Camera features are accessible through VMS platforms
- Simultaneous multiple video streams
- 10x digital zoom capability through client-side dewarping
- H.264 / MJPEG streaming with multiple quality levels
- Optimizes bandwidth and storage utilization
- Intuitive web-based interface for viewing and configuration
- Supported by major VMS / NVR systems
- ONVIF profile S and G conformant

# Evolution 05 Mini



## 360° Night Camera

The next step in 360° total situational awareness

| Model                            | EVO-05-LIN (White)  |
|----------------------------------|---|
| <strong>General</strong>         |   |
| Lens Field of View               | 180° Horizontal, 168° Vertical  |
| Image Sensor                     | 2592 H x 1944 V, 5 MP,<br>1/2.5-inch CMOS Sensor  |
| Lens                             | 185° / F2.0   |
| Minimum Illumination             | 0.2 lux = 50 IRE F/2.0 (6500 K)   |
| Frame Rate                       | 30 fps for 1 MP and ¼ MP resolution<br>15 fps for 2 MP resolution<br>10 fps for 4 MP full resolution                                  |
| Video Motion Detection           | 8 configurable regions  |
| Security                         | Configurable password protection and 802.1x   |
| Advanced Event Management        | Triggered by motion, HTTP event, result configurable,<br>FTP/SMTP upload and local recording  |
| Networking                       | TCP/IP, HTTP, DHCP, DNS, NTP, FTP, SMTP, RTSP, uPNP and SNMP  |
| Privacy Regions                  | 10 configurable privacy regions   |
| MicroSD Card                     | Built-in microSD card slot. Supports cards up to 128 GB capacity. Speed class 10 or higher required<br>SD Card recording and ONVIF G. |
| White Balance Range              | Auto White Balance (Range = approximately 2500 K ~ 8000 K)  |
| <strong>Video</strong>           |   |
| Video Stream 1 Codec             | H.264 High, Level 5 / MJPEG (streams configurable)  |
| Video Stream 1 Compression Level | Multi-levels of compression and frame rate adjustment   |
| Video Stream 1 Pixel Resolution  | Fisheyes at: 4 MP (2144 x 1944), 2 MP (1488 x 1360),<br>1 MP (1056 x 960), ¼ MP (528 x 480)   |
| Video Stream 2 Codec             | H.264 High, Level 5 / MJPEG (streams configurable)  |
| Video Stream 2 Compression Level | Multi-levels of compression and frame rate adjustment   |
| Video Stream 2 Pixel Resolution  | Fisheyes at: 4 MP (2144 x 1944), 2 MP (1488 x 1360),<br>1 MP (1056 x 960), ¼ MP (528 x 480)   |
| Video Stream 3 Codec             | MJPEG   |
| Video Stream 3 Compression Level | Multi-levels of compression and frame rate adjustment   |
| Video Stream 3 Pixel Resolution  | Fisheye at: ¼ MP (528 x 480)  |
| Maximum Frame Rate               | 30 fps  |
| Image Control                    | Settings: brightness / contrast / saturation / exposure compensation,<br>compression quality and wall / ceiling / table mount         |
| Image Enhancement                | Electronic WDR 60dB   |
| PTZ Functionality                | 10x zoom with Oncam 3D client-side dewarping software   |
| VMS / NVR Support                | Contact Oncam Sales for the supported VMS / NVR list  |
| Web Browser Compatibility        | Internet Explorer 9, Edge 25, Firefox 23 and Chrome 29 or above. Plug-in required for full functional-<br>ity                         |
| Unicast                          | Up to 20 simultaneous users depending on the resolution settings  |
| Multicast                        | Supported for all H.264 camera streams  |
| Bit Rate Control                 | Options include Variable Bit Rate Controls, Constant Bit Rate Control and Constant Quality Control                                    |
| <strong>Electrical</strong>      |   |
| Connection                       | Flying lead - RJ45 plug   |
| Network Cable Type               | CAT5 or better for 100Base-TX   |
| Power Input                      | Power over Ethernet (PoE), IEEE standard 802.3af  |
| Power Consumption (maximum)      | 4.13 W  |

# Evolution 05 Mini







## 360° Night Camera

The next step in 360° total situational awareness

| Mechanical                    |                                    |
|-------------------------------|------------------------------------|
| Camera Mount                  | Surface mount                      |
| Weight                        | 0.22 kg (0.48 lbs)                 |
| Dimensions (Diameter x Depth) | 107 mm (4.2 in.) x 34 mm (1.3 in.) |
| Housing Material              | Polymer                            |

| Environmental               |                            |
|-----------------------------|----------------------------|
| Operating Temperature Range | 0 to +40°C (-32 to +104°F) |
| Operating Humidity          | Up to 98% non-condensing   |
| Ingress Protection          | IP40                       |

| Certifications |   |
|----------------|---|
| Approvals      | IEEE802.3af, CE, AS/NZS CISPR 32:2015/COR1:2016, CISPR 24:2010 +A1:2015 (Class A), FCC, ICES-003 Issue 6-2016, KCC, CU, RCM, SASO, IP40<br>UL 60950-1(ed.2) & CAN/CSA C22.2 No. 60950-1-07, UL/IEC 62368-1, RoHS, REACH |

| Accessories   |                    |   |
|---|--------------------|---|
|   | Part Number        | Description   |
|   | OBE-11-IWA (White) | IK10+ vandal resistant bubble trim<br><br>The bubble trim is made of optical grade polymer.   |
|  | OBE-16-OWA (White) | M20 conduit back box<br><br>Fitted for the camera back and provides three entry points for easy cabling through M20 size conduits. Coil excess cable within back box. |
|  | OBE-13-IBA         | Pendant Mount Adapter<br><br>M32 female thread; supplied with M32 to 1½ NPT male thread adaptor. Fit onto the camera back.  |
|  | OBE-17-IWA (White) | Indoor Mounting Kit<br><br>Includes a Pendant Mount Adapter and Conduit Back Box.   |


# Evolution 05 Mini



## 360° Night Camera

The next step in 360° total situational awareness

### Dimensions



©2014 - 2020 Oncam Global Group AG. All rights reserved.

Oncam Grandeye is the trade name of Oncam Global Group AG. Specifications and configurations subject to change without notice.

EVO-05-L#N-02\_2020.11